

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



MAPRENAL BF 892 ULF

Version	Revision Date:	SDS Number:	Date of last issue: 30.05.2022
3.0	17.10.2022	9515159-00004	Date of first issue: 06.09.2021

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : MAPRENAL BF 892 ULF

Product code : FG044

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-
stance/Mixture : Binding agent, Coatings, Curing chemical, Industrial use

Recommended restrictions
on use : Not applicable

1.3 Details of the supplier of the safety data sheet

Company : Prefere Melamines GmbH
Alt Fechenheim 34
60386 Frankfurt am Main, Germany

Telephone : +49 69 6051040 2319

E-mail address of person
responsible for the SDS : reach-melamines@prefere.com

1.4 Emergency telephone number

Emergency telephone number
(24 h / 365 d):
Europe: +49 6132 84463
(GBK ID 92706)
Rest of World: +1 352 323 3500
(GBK/Infotrac ID 92706)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

**Classification (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK
SI 2019/720, and UK SI 2020/1567)**

Skin irritation, Category 2 H315: Causes skin irritation.

Eye irritation, Category 2 H319: Causes serious eye irritation.

Specific target organ toxicity - single ex-
posure, Category 3 H335: May cause respiratory irritation.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



MAPRENAL BF 892 ULF

Version	Revision Date:	SDS Number:	Date of last issue: 30.05.2022
3.0	17.10.2022	9515159-00004	Date of first issue: 06.09.2021

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

Hazard pictograms :



Signal word : Warning

Hazard statements : H315 Causes skin irritation.
H319 Causes serious eye irritation.
H335 May cause respiratory irritation.

Precautionary statements : **Prevention:**
P261 Avoid breathing spray.
P264 Wash skin thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves/ eye protection/ face protection.

Response:
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.
P337 + P313 If eye irritation persists: Get medical advice/ attention.

Hazardous components which must be listed on the label:

2-Ethylhexan-1-ol
Butan-1-ol

Additional Labelling

|| EUH208 Contains Formaldehyde.
May produce an allergic reaction.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Vapours may form explosive mixture with air.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : Benzoguanamine formaldehyde resin, alkylated

Special ingredients : Specification for free Formaldehyde content: < 0.1 %

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



MAPRENAL BF 892 ULF

Version 3.0 Revision Date: 17.10.2022 SDS Number: 9515159-00004 Date of last issue: 30.05.2022
Date of first issue: 06.09.2021

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
2-Ethylhexan-1-ol	104-76-7 203-234-3	Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Irrit. 2; H319 STOT SE 3; H335	>= 20 - < 30
Butan-1-ol	71-36-3 200-751-6 603-004-00-6 01-2119484630-38	Flam. Liq. 3; H226 Acute Tox. 4; H302 Skin Irrit. 2; H315 Eye Dam. 1; H318 STOT SE 3; H335 STOT SE 3; H336	>= 1 - < 3
Formaldehyde	50-00-0 200-001-8 605-001-00-5 01-2119488953-20	Acute Tox. 3; H301 Acute Tox. 2; H330 Acute Tox. 3; H311 Skin Corr. 1B; H314 Eye Dam. 1; H318 Skin Sens. 1A; H317 Muta. 2; H341 Carc. 1B; H350 STOT SE 3; H335 specific concentra- tion limit Skin Corr. 1B; H314 >= 25 % Skin Irrit. 2; H315 5 - < 25 % Eye Irrit. 2; H319 5 - < 25 % STOT SE 3; H335 >= 5 % Skin Sens. 1A; H317 >= 0.2 %	< 0.1

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : In the case of accident or if you feel unwell, seek medical advice immediately.
When symptoms persist or in all cases of doubt seek medical

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



MAPRENAL BF 892 ULF

Version	Revision Date:	SDS Number:	Date of last issue: 30.05.2022
3.0	17.10.2022	9515159-00004	Date of first issue: 06.09.2021

advice.

- Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).
- If inhaled : If inhaled, remove to fresh air.
Get medical attention if symptoms occur.
- In case of skin contact : In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.
Get medical attention.
Wash clothing before reuse.
Thoroughly clean shoes before reuse.
- In case of eye contact : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.
If easy to do, remove contact lens, if worn.
Get medical attention.
- If swallowed : If swallowed, DO NOT induce vomiting.
Get medical attention if symptoms occur.
Rinse mouth thoroughly with water.

4.2 Most important symptoms and effects, both acute and delayed

- Risks : Causes skin irritation.
Causes serious eye irritation.
May cause respiratory irritation.

4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : Treat symptomatically and supportively.
-

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing media : Water spray
Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical
- Unsuitable extinguishing media : High volume water jet

5.2 Special hazards arising from the substance or mixture

- Specific hazards during fire-fighting : Do not use a solid water stream as it may scatter and spread fire.
Flash back possible over considerable distance.
Vapours may form explosive mixtures with air.
-

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



MAPRENAL BF 892 ULF

Version	Revision Date:	SDS Number:	Date of last issue: 30.05.2022
3.0	17.10.2022	9515159-00004	Date of first issue: 06.09.2021

Exposure to combustion products may be a hazard to health.

Hazardous combustion products : Carbon oxides
Formaldehyde
Nitrogen oxides (NOx)

5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment.

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do so.
Evacuate area.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Remove all sources of ignition.
Use personal protective equipment.
Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).

6.2 Environmental precautions

Environmental precautions : Avoid release to the environment.
Prevent further leakage or spillage if safe to do so.
Prevent spreading over a wide area (e.g. by containment or oil barriers).
Retain and dispose of contaminated wash water.
Local authorities should be advised if significant spillages cannot be contained.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Non-sparking tools should be used.
Soak up with inert absorbent material.
Suppress (knock down) gases/vapours/mists with a water spray jet.
For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container.
Clean up remaining materials from spill with suitable absorbent.
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.
Sections 13 and 15 of this SDS provide information regarding

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



MAPRENAL BF 892 ULF

Version	Revision Date:	SDS Number:	Date of last issue: 30.05.2022
3.0	17.10.2022	9515159-00004	Date of first issue: 06.09.2021

certain local or national requirements.

6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

- Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.
- Local/Total ventilation : If sufficient ventilation is unavailable, use with local exhaust ventilation.
- Advice on safe handling : Do not breathe decomposition products.
- Do not get on skin or clothing.
Avoid breathing spray.
Do not swallow.
Do not get in eyes.
Wash skin thoroughly after handling.
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment
Keep container tightly closed.
Already sensitised individuals, and those susceptible to asthma, allergies, chronic or recurrent respiratory disease, should consult their physician regarding working with respiratory irritants or sensitisers.
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Take precautionary measures against static discharges.
Take care to prevent spills, waste and minimize release to the environment.
- Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place. When using do not eat, drink or smoke. Wash contaminated clothing before re-use.

7.2 Conditions for safe storage, including any incompatibilities

- Requirements for storage areas and containers : Keep in properly labelled containers. Store locked up. Keep tightly closed. Keep in a cool, well-ventilated place. Store in accordance with the particular national regulations. Keep away from heat and sources of ignition.
- Advice on common storage : Do not store with the following product types:
Strong oxidizing agents
Explosives
Gases

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



MAPRENAL BF 892 ULF

Version 3.0 Revision Date: 17.10.2022 SDS Number: 9515159-00004 Date of last issue: 30.05.2022
Date of first issue: 06.09.2021

7.3 Specific end use(s)

Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
2-Ethylhexan-1-ol	104-76-7	TWA	1 ppm 5.4 mg/m ³	GB EH40
		TWA	1 ppm 5.4 mg/m ³	2017/164/EU
	Further information: Indicative			
Butan-1-ol	71-36-3	STEL	50 ppm 154 mg/m ³	GB EH40
		Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.		
Formaldehyde	50-00-0	TWA	2 ppm 2.5 mg/m ³	GB EH40
		Further information: Capable of causing cancer and/or heritable genetic damage.		
		STEL	2 ppm 2.5 mg/m ³	GB EH40
	Further information: Capable of causing cancer and/or heritable genetic damage.			
		TWA	0.3 ppm 0.37 mg/m ³	2004/37/EC
	Further information: Dermal sensitisation, Carcinogens or mutagens			
		STEL	0.6 ppm 0.74 mg/m ³	2004/37/EC
	Further information: Dermal sensitisation, Carcinogens or mutagens			

Occupational exposure limits of decomposition products

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Formaldehyde	50-00-0	TWA	2 ppm 2.5 mg/m ³	GB EH40
		Further information: Capable of causing cancer and/or heritable genetic damage.		
		STEL	2 ppm 2.5 mg/m ³	GB EH40
	Further information: Capable of causing cancer and/or heritable genetic damage.			
		TWA	0.3 ppm 0.37 mg/m ³	2004/37/EC
	Further information: Dermal sensitisation, Carcinogens or mutagens			

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



MAPRENAL BF 892 ULF

Version 3.0 Revision Date: 17.10.2022 SDS Number: 9515159-00004 Date of last issue: 30.05.2022
Date of first issue: 06.09.2021

		STEL	0.6 ppm 0.74 mg/m ³	2004/37/EC
	Further information: Dermal sensitisation, Carcinogens or mutagens			
Butan-1-ol	71-36-3	STEL	50 ppm 154 mg/m ³	GB EH40
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			

Derived No Effect Level (DNEL):

Substance name	End Use	Exposure routes	Potential health effects	Value
2-Ethylhexan-1-ol	Workers	Inhalation	Long-term systemic effects	12.8 mg/m ³
	Workers	Inhalation	Long-term local effects	53.2 mg/m ³
	Workers	Inhalation	Acute local effects	53.2 mg/m ³
	Workers	Skin contact	Long-term systemic effects	23 mg/kg bw/day
	Workers	Inhalation	Acute local effects	106.4 mg/m ³
	Consumers	Inhalation	Long-term systemic effects	2.3 mg/m ³
	Consumers	Inhalation	Long-term local effects	26.6 mg/m ³
	Consumers	Inhalation	Acute local effects	26.6 mg/m ³
	Consumers	Skin contact	Long-term systemic effects	11.4 mg/kg bw/day
Butan-1-ol	Consumers	Ingestion	Long-term systemic effects	1.1 mg/kg bw/day
	Workers	Inhalation	Long-term local effects	310 mg/m ³
	Consumers	Ingestion	Long-term systemic effects	3.125 mg/kg bw/day
Formaldehyde	Consumers	Inhalation	Long-term local effects	55 mg/m ³
	Workers	Inhalation	Long-term systemic effects	9 mg/m ³
	Workers	Inhalation	Long-term local effects	0.375 mg/m ³
	Workers	Skin contact	Long-term systemic effects	240 mg/kg bw/day
	Workers	Inhalation	Acute local effects	0.75 mg/m ³
	Consumers	Inhalation	Long-term systemic effects	3.2 mg/m ³
	Consumers	Skin contact	Long-term systemic effects	102 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	4.1 mg/kg bw/day
	Workers	Skin contact	Long-term local effects	0.037 mg/cm ²
Consumers	Inhalation	Long-term local effects	0.1 mg/m ³	

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



MAPRENAL BF 892 ULF

Version 3.0 Revision Date: 17.10.2022 SDS Number: 9515159-00004 Date of last issue: 30.05.2022
Date of first issue: 06.09.2021

	Consumers	Skin contact	Long-term local effects	0.012 mg/cm ²
--	-----------	--------------	-------------------------	--------------------------

Predicted No Effect Concentration (PNEC):

Substance name	Environmental Compartment	Value
2-Ethylhexan-1-ol	Fresh water	0.017 mg/l
	Intermittent use/release	0.17 mg/l
	Marine water	0.002 mg/l
	Sewage treatment plant	10 mg/l
	Fresh water sediment	0.284 mg/kg dry weight (d.w.)
	Marine sediment	0.028 mg/kg dry weight (d.w.)
	Soil	0.047 mg/kg dry weight (d.w.)
Butan-1-ol	Oral (Secondary Poisoning)	55 mg/kg food
	Fresh water	0.082 mg/l
	Marine water	0.008 mg/l
	Intermittent use/release	2.25 mg/l
	Sewage treatment plant	2476 mg/l
	Fresh water sediment	0.178 mg/kg
Formaldehyde	Marine sediment	0.018 mg/kg
	Soil	0.015 mg/kg
	Fresh water	0.44 mg/l
	Marine water	0.44 mg/l
	Intermittent use/release	4.44 mg/l
	Sewage treatment plant	0.19 mg/l
	Fresh water sediment	2.3 mg/kg
	Marine sediment	2.3 mg/kg
	Soil	0.2 mg/kg

8.2 Exposure controls

Engineering measures

Processing may form hazardous compounds (see section 10).
Minimize workplace exposure concentrations.
If sufficient ventilation is unavailable, use with local exhaust ventilation.

Personal protective equipment

Eye/face protection : Wear the following personal protective equipment:
Safety goggles
Equipment should conform to BS EN 166

Hand protection

Material : Nitrile rubber
Break through time : 30 - < 60 min
Glove thickness : 0.12 mm
Directive : Equipment should conform to BS EN 374
Protective index : Class 2

Material : Nitrile rubber
Break through time : > 480 min

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



MAPRENAL BF 892 ULF

Version	Revision Date:	SDS Number:	Date of last issue: 30.05.2022
3.0	17.10.2022	9515159-00004	Date of first issue: 06.09.2021

Glove thickness : 0.38 mm
Directive : Equipment should conform to BS EN 374
Protective index : Class 6

Material : butyl-rubber
Break through time : > 480 min
Glove thickness : 0.3 mm
Directive : Equipment should conform to BS EN 374
Protective index : Class 6

Material : Fluorinated rubber
Break through time : > 480 min
Glove thickness : 0.7 mm
Directive : Equipment should conform to BS EN 374
Protective index : Class 6

Remarks : Choose gloves to protect hands against chemicals depending on the concentration and quantity of the hazardous substance and specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.
Wear the following personal protective equipment:
If assessment demonstrates that there is a risk of explosive atmospheres or flash fires, use flame retardant antistatic protective clothing.
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).

Respiratory protection : If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection.
Equipment should conform to BS EN 14387

Filter type : Combined inorganic gas/vapour and organic vapour type (AB)

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : liquid
Colour : colourless
Odour : alcohol-like
Odour Threshold : No data available

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



MAPRENAL BF 892 ULF

Version	Revision Date:	SDS Number:	Date of last issue: 30.05.2022
3.0	17.10.2022	9515159-00004	Date of first issue: 06.09.2021

pH	:	No data available
Melting point/freezing point	:	No data available
Initial boiling point and boiling range	:	> 120 °C
Flash point	:	78.5 °C Method: ISO 3679, Tag closed cup
Evaporation rate	:	No data available
Flammability (solid, gas)	:	Not applicable
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapour pressure	:	48 Pa (20 °C) Solvent
Relative vapour density	:	No data available
Density	:	1.04 g/cm ³ (23 °C) Method: DIN 12791
Solubility(ies) Water solubility	:	insoluble
Partition coefficient: n-octanol/water	:	Not applicable
Auto-ignition temperature	:	270 °C Solvent
Decomposition temperature	:	The substance or mixture is not classified self-reactive.
Viscosity Viscosity, dynamic	:	1,200 - 2,100 mPa.s (23 °C) Method: ISO 3219
Viscosity, kinematic	:	No data available
Explosive properties	:	Not explosive
Oxidizing properties	:	The substance or mixture is not classified as oxidizing.

9.2 Other information

Flammability (liquids)	:	No data available
------------------------	---	-------------------

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



MAPRENAL BF 892 ULF

Version	Revision Date:	SDS Number:	Date of last issue: 30.05.2022
3.0	17.10.2022	9515159-00004	Date of first issue: 06.09.2021

Metal corrosion rate : Not corrosive to metals

Particle size : Not applicable

SECTION 10: Stability and reactivity

10.1 Reactivity

Not classified as a reactivity hazard.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : Combustible liquid.
Vapours may form explosive mixture with air.
Can react with strong oxidizing agents.
Hazardous decomposition products will be formed at elevated temperatures.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : Oxidizing agents

10.6 Hazardous decomposition products

Thermal decomposition : Formaldehyde
Butan-1-ol

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Information on likely routes of exposure : Inhalation
Skin contact
Ingestion
Eye contact

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity : Acute toxicity estimate: > 2,000 mg/kg
Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: Calculation method

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



MAPRENAL BF 892 ULF

Version 3.0 Revision Date: 17.10.2022 SDS Number: 9515159-00004 Date of last issue: 30.05.2022
Date of first issue: 06.09.2021

Components:

2-Ethylhexan-1-ol:

Acute oral toxicity : LD50 (Rat): 2,047 mg/kg
Acute inhalation toxicity : LC50 (Rat): > 0.89 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Acute dermal toxicity : LD50 (Rabbit): > 3,000 mg/kg
Method: OECD Test Guideline 402
Assessment: The substance or mixture has no acute dermal toxicity

Butan-1-ol:

Acute oral toxicity : LD50 (Rat): 790 mg/kg
Acute inhalation toxicity : LC0 (Rat): > 17.76 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Acute dermal toxicity : LD50 (Rabbit): 3,430 mg/kg

Formaldehyde:

Acute oral toxicity : Acute toxicity estimate: 100 mg/kg
Method: Expert judgement
Acute inhalation toxicity : Acute toxicity estimate: 100 ppm
Exposure time: 4 h
Test atmosphere: gas
Method: Expert judgement
Acute dermal toxicity : LD50 (Rabbit): 270 mg/kg

Skin corrosion/irritation

Causes skin irritation.

Components:

2-Ethylhexan-1-ol:

Species : Rabbit
Method : OECD Test Guideline 404
Result : Skin irritation

Butan-1-ol:

Species : Rabbit
Result : Skin irritation

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



MAPRENAL BF 892 ULF

Version 3.0 Revision Date: 17.10.2022 SDS Number: 9515159-00004 Date of last issue: 30.05.2022
Date of first issue: 06.09.2021

Formaldehyde:

Species : Rabbit
Method : OECD Test Guideline 404
Result : Corrosive after 3 minutes to 1 hour of exposure

Serious eye damage/eye irritation

Causes serious eye irritation.

Components:

2-Ethylhexan-1-ol:

Species : Rabbit
Method : OECD Test Guideline 405
Result : Irritation to eyes, reversing within 21 days

Butan-1-ol:

Species : Rabbit
Method : OECD Test Guideline 405
Result : Irreversible effects on the eye

Formaldehyde:

Species : Rabbit
Result : Irreversible effects on the eye

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Components:

Butan-1-ol:

Test Type : Maximisation Test
Exposure routes : Skin contact
Species : Guinea pig
Result : negative
Remarks : Based on data from similar materials

Formaldehyde:

Test Type : Local lymph node assay (LLNA)
Exposure routes : Skin contact
Species : Mouse
Method : OECD Test Guideline 429
Result : positive

Assessment : Probability or evidence of high skin sensitisation rate in humans

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



MAPRENAL BF 892 ULF

Version	Revision Date:	SDS Number:	Date of last issue: 30.05.2022
3.0	17.10.2022	9515159-00004	Date of first issue: 06.09.2021

Germ cell mutagenicity

Not classified based on available information.

Components:

2-Ethylhexan-1-ol:

Genotoxicity in vitro	:	Test Type: Bacterial reverse mutation assay (AMES) Method: OECD Test Guideline 471 Result: negative
Genotoxicity in vivo	:	Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay) Species: Mouse Application Route: Intraperitoneal injection Result: negative

Butan-1-ol:

Genotoxicity in vitro	:	Test Type: In vitro mammalian cell gene mutation test Method: OECD Test Guideline 476 Result: negative
Genotoxicity in vivo	:	Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay) Species: Mouse Application Route: Ingestion Method: OECD Test Guideline 474 Result: negative

Formaldehyde:

Genotoxicity in vitro	:	Test Type: Bacterial reverse mutation assay (AMES) Result: positive
		Test Type: Chromosome aberration test in vitro Result: positive
Genotoxicity in vivo	:	Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay) Species: Rat Application Route: Inhalation Result: positive
Germ cell mutagenicity- Assessment	:	Positive result(s) from in vivo mammalian somatic cell mutagenicity tests.

Carcinogenicity

Not classified based on available information.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



MAPRENAL BF 892 ULF

Version 3.0 Revision Date: 17.10.2022 SDS Number: 9515159-00004 Date of last issue: 30.05.2022
Date of first issue: 06.09.2021

Components:

2-Ethylhexan-1-ol:

Species : Rat
Application Route : Ingestion
Exposure time : 2 Years
Result : negative

Formaldehyde:

Species : Rat
Application Route : inhalation (gas)
Exposure time : 28 Months
Result : positive

Carcinogenicity - Assessment : Sufficient evidence of carcinogenicity in animal experiments

Reproductive toxicity

Not classified based on available information.

Components:

2-Ethylhexan-1-ol:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 416
Result: negative

Effects on foetal development : Test Type: Embryo-foetal development
Species: Rat
Application Route: Skin contact
Method: OECD Test Guideline 414
Result: negative

Butan-1-ol:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: inhalation (vapour)
Method: OECD Test Guideline 416
Result: negative
Remarks: Based on data from similar materials

Effects on foetal development : Test Type: Embryo-foetal development
Species: Rat
Application Route: Ingestion
Result: negative

Formaldehyde:

Effects on foetal development : Test Type: Embryo-foetal development

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



MAPRENAL BF 892 ULF

Version 3.0 Revision Date: 17.10.2022 SDS Number: 9515159-00004 Date of last issue: 30.05.2022
Date of first issue: 06.09.2021

|| ment Species: Rat
Application Route: inhalation (gas)
Result: negative

STOT - single exposure

May cause respiratory irritation.

Components:

2-Ethylhexan-1-ol:

|| Assessment : May cause respiratory irritation.

Butan-1-ol:

|| Assessment : May cause respiratory irritation., May cause drowsiness or dizziness.

Formaldehyde:

|| Assessment : May cause respiratory irritation.

STOT - repeated exposure

Not classified based on available information.

Components:

2-Ethylhexan-1-ol:

|| Assessment : No significant health effects observed in animals at concentrations of 1 mg/l/6h/d or less.

Formaldehyde:

|| Assessment : No significant health effects observed in animals at concentrations of 250 ppmV/6h/d or less.

Repeated dose toxicity

Components:

2-Ethylhexan-1-ol:

|| Species : Rat
NOAEL : 250 mg/kg
Application Route : Ingestion
Exposure time : 90 Days
Method : OECD Test Guideline 408

|| Species : Rat
NOAEL : 0.6384 mg/l
Application Route : inhalation (vapour)
Exposure time : 90 Days
Method : OECD Test Guideline 413

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



MAPRENAL BF 892 ULF

Version	Revision Date:	SDS Number:	Date of last issue: 30.05.2022
3.0	17.10.2022	9515159-00004	Date of first issue: 06.09.2021

Butan-1-ol:

Species	: Rat
NOAEL	: 125 mg/kg
Application Route	: Ingestion
Exposure time	: 13 Weeks

Formaldehyde:

Species	: Rat
NOAEL	: 6 ppm
LOAEL	: 10 ppm
Application Route	: inhalation (gas)
Exposure time	: 28 Days

Aspiration toxicity

Not classified based on available information.

Components:

Butan-1-ol:

The substance or mixture causes concern owing to the assumption that it causes a human aspiration toxicity hazard.

SECTION 12: Ecological information

12.1 Toxicity

Components:

2-Ethylhexan-1-ol:

Toxicity to fish	: LC50 (Pimephales promelas (fathead minnow)): 28.2 mg/l Exposure time: 96 h Method: OECD Test Guideline 203
Toxicity to daphnia and other aquatic invertebrates	: EC50 (Daphnia magna (Water flea)): 39 mg/l Exposure time: 48 h Method: Directive 67/548/EEC, Annex V, C.2.
Toxicity to algae/aquatic plants	: ErC50 (Desmodesmus subspicatus (green algae)): 16.6 mg/l Exposure time: 72 h Method: Directive 67/548/EEC, Annex V, C.3.
	EC10 (Desmodesmus subspicatus (green algae)): 16.6 mg/l Exposure time: 72 h Method: Directive 67/548/EEC, Annex V, C.3.

Butan-1-ol:

Toxicity to fish	: LC50 (Pimephales promelas (fathead minnow)): 1,376 mg/l Exposure time: 96 h Method: OECD Test Guideline 203
------------------	---

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



MAPRENAL BF 892 ULF

Version 3.0 Revision Date: 17.10.2022 SDS Number: 9515159-00004 Date of last issue: 30.05.2022
Date of first issue: 06.09.2021

Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): 1,328 mg/l Exposure time: 48 h Method: OECD Test Guideline 202
Toxicity to algae/aquatic plants	:	ErC50 (Pseudokirchneriella subcapitata (green algae)): 225 mg/l Exposure time: 96 h Method: OECD Test Guideline 201
Toxicity to microorganisms	:	EC50 (Pseudomonas putida): 4,390 mg/l Exposure time: 17 h
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	:	NOEC: 4.1 mg/l Exposure time: 21 d Species: Daphnia magna (Water flea) Method: OECD Test Guideline 211

Formaldehyde:

Toxicity to fish	:	LC50 : 6.7 mg/l Exposure time: 96 h Remarks: Based on data from similar materials
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia pulex (Water flea)): 5.8 mg/l Exposure time: 48 h Method: OECD Test Guideline 202
Toxicity to algae/aquatic plants	:	EC50 (Desmodesmus subspicatus (green algae)): 4.89 mg/l Exposure time: 72 h Method: OECD Test Guideline 201
Toxicity to microorganisms	:	EC50 : 34.1 mg/l Exposure time: 120 h
Toxicity to fish (Chronic toxicity)	:	NOEC: \geq 48 mg/l Exposure time: 28 d Species: Oryzias latipes (Orange-red killifish)
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	:	NOEC: \geq 6.4 mg/l Exposure time: 21 d Species: Daphnia magna (Water flea) Method: OECD Test Guideline 211

12.2 Persistence and degradability

Components:

2-Ethylhexan-1-ol:

Biodegradability	:	Result: Readily biodegradable. Biodegradation: 79 - 99.9 % Exposure time: 14 d
------------------	---	--

Butan-1-ol:

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



MAPRENAL BF 892 ULF

Version	Revision Date:	SDS Number:	Date of last issue: 30.05.2022
3.0	17.10.2022	9515159-00004	Date of first issue: 06.09.2021

Biodegradability : Result: Readily biodegradable.
Biodegradation: 92 %
Exposure time: 20 d

Formaldehyde:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 91 %
Exposure time: 14 d
Method: OECD Test Guideline 301C
Remarks: Based on data from similar materials

12.3 Bioaccumulative potential

Components:

2-Ethylhexan-1-ol:

Partition coefficient: n-octanol/water : log Pow: 2.9

Butan-1-ol:

Partition coefficient: n-octanol/water : log Pow: 1

Formaldehyde:

Partition coefficient: n-octanol/water : log Pow: 0.35

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

No data available

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



MAPRENAL BF 892 ULF

Version	Revision Date:	SDS Number:	Date of last issue: 30.05.2022
3.0	17.10.2022	9515159-00004	Date of first issue: 06.09.2021

SECTION 13: Disposal considerations

13.1 Waste treatment methods

- Product : Dispose of in accordance with local regulations.
According to the European Waste Catalogue, Waste Codes are not product specific, but application specific.
Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities.
- Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.
Empty containers retain residue and can be dangerous.
Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death.
If not otherwise specified: Dispose of as unused product.
-

SECTION 14: Transport information

14.1 UN number

- | | |
|------|-------------------------------------|
| ADN | : Not regulated as a dangerous good |
| ADR | : Not regulated as a dangerous good |
| RID | : Not regulated as a dangerous good |
| IMDG | : Not regulated as a dangerous good |
| IATA | : UN 3334 |

14.2 UN proper shipping name

- | | |
|------|--|
| ADN | : Not regulated as a dangerous good |
| ADR | : Not regulated as a dangerous good |
| RID | : Not regulated as a dangerous good |
| IMDG | : Not regulated as a dangerous good |
| IATA | : Aviation regulated liquid, n.o.s.
(2-Ethylhexan-1-ol) |

14.3 Transport hazard class(es)

- | | |
|------|-------------------------------------|
| ADN | : Not regulated as a dangerous good |
| ADR | : Not regulated as a dangerous good |
| RID | : Not regulated as a dangerous good |
| IMDG | : Not regulated as a dangerous good |
| IATA | : 9 |

14.4 Packing group

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



MAPRENAL BF 892 ULF

Version	Revision Date:	SDS Number:	Date of last issue: 30.05.2022
3.0	17.10.2022	9515159-00004	Date of first issue: 06.09.2021

ADN	:	Not regulated as a dangerous good
ADR	:	Not regulated as a dangerous good
RID	:	Not regulated as a dangerous good
IMDG	:	Not regulated as a dangerous good

IATA (Cargo)

Packing instruction (cargo aircraft)	:	964
Packing instruction (LQ)	:	Y964
Packing group	:	III
Labels	:	Miscellaneous

IATA (Passenger)

Packing instruction (passenger aircraft)	:	964
Packing instruction (LQ)	:	Y964
Packing group	:	III
Labels	:	Miscellaneous

14.5 Environmental hazards

ADN	:	Not regulated as a dangerous good
ADR	:	Not regulated as a dangerous good
RID	:	Not regulated as a dangerous good
IMDG	:	Not regulated as a dangerous good

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Remarks : Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

UK REACH List of restrictions (Annex 17)	:	Conditions of restriction for the following entries should be considered: Number on list 3 Formaldehyde (Number on list 72, 28)
UK REACH Candidate list of substances of very high concern (SVHC) for Authorisation	:	Not applicable
The Persistent Organic Pollutants Regulations (retained)	:	Not applicable

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758



MAPRENAL BF 892 ULF

Version	Revision Date:	SDS Number:	Date of last issue: 30.05.2022
3.0	17.10.2022	9515159-00004	Date of first issue: 06.09.2021

Regulation (EU) 2019/1021 as amended for Great Britain)

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

UK REACH List of substances subject to authorisation (Annex XIV) : Not applicable

GB Export and import of hazardous chemicals - Prior Informed Consent (PIC) Regulation : Not applicable

Control of Major Accident Hazards Regulations 2015 (COMAH)
Not applicable

The components of this product are reported in the following inventories:

REACH : All ingredients (pre-)registered or exempt.

TSCA : On or in compliance with the active portion of the TSCA inventory

AIC : All ingredients listed or exempt.

DSL : All chemical substances in this product comply with the CEPA 1999 and NSNR and are on or exempt from listing on the Canadian Domestic Substances List (DSL).

ENCS : On the inventory, or in compliance with the inventory

ISHL : On the inventory, or in compliance with the inventory

KECI : All ingredients listed, exempt or notified.

PICCS : All ingredients listed or exempt.

IECSC : All ingredients listed or exempt.

NZIoC : All ingredients listed or exempt.

TECI : On the inventory, or in compliance with the inventory

15.2 Chemical safety assessment

A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

Other information : Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



MAPRENAL BF 892 ULF

Version	Revision Date:	SDS Number:	Date of last issue: 30.05.2022
3.0	17.10.2022	9515159-00004	Date of first issue: 06.09.2021

Full text of H-Statements

H226	: Flammable liquid and vapour.
H301	: Toxic if swallowed.
H302	: Harmful if swallowed.
H311	: Toxic in contact with skin.
H314	: Causes severe skin burns and eye damage.
H315	: Causes skin irritation.
H317	: May cause an allergic skin reaction.
H318	: Causes serious eye damage.
H319	: Causes serious eye irritation.
H330	: Fatal if inhaled.
H332	: Harmful if inhaled.
H335	: May cause respiratory irritation.
H336	: May cause drowsiness or dizziness.
H341	: Suspected of causing genetic defects.
H350	: May cause cancer.

Full text of other abbreviations

Acute Tox.	: Acute toxicity
Carc.	: Carcinogenicity
Eye Dam.	: Serious eye damage
Eye Irrit.	: Eye irritation
Flam. Liq.	: Flammable liquids
Muta.	: Germ cell mutagenicity
Skin Corr.	: Skin corrosion
Skin Irrit.	: Skin irritation
Skin Sens.	: Skin sensitisation
STOT SE	: Specific target organ toxicity - single exposure
2004/37/EC	: Europe. Directive 2004/37/EC on the protection of workers from the risks related to exposure to carcinogens or mutagens at work
2017/164/EU	: Europe. Commission Directive 2017/164/EU establishing a fourth list of indicative occupational exposure limit values
GB EH40	: UK. EH40 WEL - Workplace Exposure Limits
2004/37/EC / STEL	: Short term exposure limit
2004/37/EC / TWA	: Long term exposure limit
2017/164/EU / TWA	: Limit Value - eight hours
GB EH40 / TWA	: Long-term exposure limit (8-hour TWA reference period)
GB EH40 / STEL	: Short-term exposure limit (15-minute reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China;

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758



MAPRENAL BF 892 ULF

Version	Revision Date:	SDS Number:	Date of last issue: 30.05.2022
3.0	17.10.2022	9515159-00004	Date of first issue: 06.09.2021

IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECl - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Further information

Sources of key data used to compile the Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Classification of the mixture:

Skin Irrit. 2	H315
Eye Irrit. 2	H319
STOT SE 3	H335

Classification procedure:

Calculation method
Calculation method
Calculation method

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

GB / EN